

10. 外形图/ OUTLINE DRAWINGS

Rev.No.	REVISION NOTE	DATE	SIGNATURE	CHECKED	NO.	PART NAME	QUANTITY	MATERIAL	FINISH	REMARKS
1					1					
2					2					

6.8±0.2
2.5±0.2

10.0±0.1
2.05±0.1

技术要求/Technic requirement

1. 额定电压/Rate voltage: 3.0V
2. 额定电流/Rate current: 90mA Max
3. 额定转速/Rate speed: 9,000rpm Min
4. 启动电压/Starting voltage: 2.3V Max
5. 端子阻抗/Terminal resistance:
31Ω ± 15% (单相/Single phase)
59Ω ± 15% (双相/Double phase)
6. 在100V直流下, 导线和壳内绝缘电阻/
At DC 100V, that lead wire and case thin out
the insulation resistance: > 10MΩ
7. 导线规格/Lead spec: AWG32 UL1571
8. 未经公差/Unmark tolerance: ± 0.1

HARDNESS	ANGLE	TOLERANCE	SCALE	DATE
	3rd	±0.1/±0.5°	10/1	100715
DESIGNED BY	CHECKED BY	APPROVED BY	<p style="font-size: 24px; font-weight: bold;">Vybronic</p> <p style="font-size: 18px; font-weight: bold;">VC1020B001D</p>	
ZX	WZX	SJS		

