

10. 外形图/Outline Drawing

PCB Land drawing

技术要求/Technical Requirements:

1. 额定电压/Rated voltage: 1.3V
2. 额定电流/Rated current: 90mA Max
3. 额定转速/Rated speed: 8500 ± 2000rpm
4. 堵转电流/Stall current: 145mA Max
5. 端子阻抗/Terminal resistance: 11Ω(±20%)
6. 启动电压/Starting voltage: 0.75V Max
7. 轴向间隙/Shaft end play: 0.1~0.3mm
8. 所有尺寸为A向压紧后的尺寸(不包括轴向间隙)
Overall length is measured after counterweight being pressed against body in direction A. (Shaft end play is not included.)
9. 未注线性公差为/Unmarked tolerance: ± 0.1mm

C. W.

Vybronic		外形图		VZ6SH1A0060711	
阶段标记	重量	比例		共 页	第 页
		5:1			
设计	郭梦秋	2010.04.03	标准化	日期	项瑞莹
校对	杨 兰	2010.04.03	批准	2010.04.03	2010.04.03
审核	靳景海	2010.04.03	批准	2010.04.03	2010.04.03
工艺	刘林兵	2010.04.03	批准	2010.04.03	2010.04.03

借 (通) 用件登记	
底图总号	
签字	
日期	

11. 修改记录/ Revision History

修改号 Rev. No.	日期 Rev. Date	页码 Page No.	修改项目 Revised Item	更改原因 Reason
A/0	2010.04.03	/	产品颁布/ Release for Production	
A/1	2020.07.01	/	changed company name from JINLONG MACHINERY to VYBRONICS, changed part # from Z6SH1A0060711 to VZ6SH1A0060711	Rebranding